For:	□ File	☐ Resubmit	☐ Approval	☐ Other
M2430CL1-H				
2.5-ton SDHV Hot	Water (Coil Heating	g Module	

Job Name:Location:Date:Tag #:Architect:Engineer:Mechanical:Distributor:	Dami		
Date: Tag #:	Mechanical:	Distributor:	
	Architect:	Engineer:	
Job Name: Location:	Date:	Tag #:	
	Job Name:	Location:	

Rep:

(Company)



(Project Manager)

Features

- Modular construction
- Multiple configurations
- Enhanced Aluminum fins
- Copper tubes
- Fully lined with closed cell insulation

Matching Modules

M2430BL1-EC1 M2430BL1-EC2 M2430BL1-ST2 M2430CL1-B/E M2430V M2430R

Indoor Unit Size

2430

Operating Range

Nominal Capacity	2.5-ton (9 kW)
Airflow Range	200 to 700 CFM
	(350 to-1200 m ³ /h)

General Data:

Rated performance	see AHRI directory*
Net coil face area	2.08 ft ² (0.19 m ²)
Tube diameter	1/2 in. (12.7 mm)
Number of rows	4
Fin density	12/in. (472/m)
Water Connection Size, ODF Sweat	7/8 in. (22.2mm)
Design pressure	150 psig (1034 kPa)
Coil Water Volume	0.9 gal (3.4 L)
Shipping Weight (Cabinet Only)	20 lbs. (9.1 kg)
Shipping Weight (Coil Only)	33 lbs. (15.0 kg)
Cabinet Dimensions (H x W x D)	17.5 x 25 x 12 in.
	(445 x 635 x 305 mm)
Coil Dimensions (H x W x D)	15.9 x 20 x 4.5 in.
	(403 x 508 x 115 mm)

^{*} www.ahridirectory.org

Optional Accessories

- ☐ Control box extension cable, 98" (2.5 m) (A01525-G02)
- ☐ Modular Refrigerant Heat Pump/AC coil (M2430CL1-B/E)
- ☐ Return air module with filter (*M2430R1*)
- ☐ Vertical base module with filter (M2430V1)
- ☐ Secondary drain pan, 2 module (*UPC-20B*)
- ☐ Secondary drain pan, 3 module (UPC-20C)
- ☐ Supply duct adapter, round (*UPC-61-2430*)
- ☐ Supply duct adapter, square (UPC-62-2430)
- ☐ Return adapter (*UPC-104-2430*)

Notes

- 1. All wiring and piping must comply with applicable local and national code.
- 2. Refer to installation manual for more information.
- 3. Refer to AHRI directory for compatible outdoor match and rated performance.

Model Number Key (available models):


the desired the property of the desired th							
M	2430	С	L	1		Х	1
Model	Nominal	Module	Configuration	Revision		Style	Options
Series	Capacity	Type	L = Left			X = Cabinet	
M =	2430 =	C =	R = Right			Only, No	1 =
Modular	24000 to	Coil				Coil	Paint
	30000						White
	Btu/hr					H = Hot	
						Water Coil	

SB-M2430CL1-H.001 (20170815)

Job Name: Location:


Date: Tag #:

REFRIGERANT COIL MODULE DIMENSIONS (LEFT HAND)



^{*} All dimensions in inches [mm]. Contact Unico for dimensions of assembled modules or for right hand dimensions

Installation Clearances



Unico, Inc. http://tech.unicosystem.com 314-481-9000 800-527-0896 sales@unicosystem.com





