	For:	☐ File	☐ Resubmit	□ Approval	☐ Other	
M3642V′ 3.5-ton Ver		Return	Plenum Mo	odule		
Job Name:				Locati	ion:	
Date:				Tag #	t:	
Architect:				Engin	neer:	
Mechanical:				Distrib	butor:	
Rep:						
(Company)				(Project Ma	Janager)	



Features

- Built in secondary drain pan with ¾-inch socket connection
- Room for optional hot water coil with access from both sides
- · Centrally located pleated filter
- Heavy-duty closed cell insulation (no exposed fiberglass insulation)
- Standard Unico System 'latch' system

Matching Modules

M3642BL1-EC1/EC2 M3642CL1-B M3642CL1-E M3642CL1-C M3642CL1-H

Indoor Unit Size

3642

General Data:

Dimensions (H x W x D)	18.25 x 38 x 17.5 in.		
	(464 x 965 x 445 mm)		
Total Return Opening	254 in ² (0.16 m ²)		
Equivalent Return Opening Diameter	18 in (406 mm)		
Filter Size (2 Filters Required)	Filter 1: 18 in x 20 in x 1 in		
	(457 mm x 508 mm)		
	Filter 2: 18 in x 18 in x 1 in		
	(457 mm x 457 mm)		
Maximum Airflow	1000 CFM (472 L/s)		
Maximum Velocity	350 FPM (1.78 m/s)		
Initial Resistance	0.4 in. wg (100 Pa)		

Model Number Key (available models):

М	3642	V	1	1
Model	Nominal	Module	Revision	Paint
Series	Capacity	Type		Color
M =	3642 =	V =		None =
Modular	36000 to	Vertical		Blank
	42000	Return		1 =
	Btu/hr	Plenum		White

Optional Accessories

- ☐ Hot water coil (*HW-3642*)
- ☐ Modular Variable Speed Air Handler (*M3642BL1-EC**)
- ☐ Secondary drain pan, 2 module (UPC-24B)
- ☐ Secondary drain pan, 3 module (UPC-24C)
- ☐ Return adapter (*UPC-104-3642*)


Notes:

1. Refer to installation manual for more information.

Job Name: Location:


Date: Tag #:

RETURN AIR PLENUM MODULE DIMENSIONS



^{*} Contact Unico for dimensions of assembled modules.

Installation Clearances



Unico, Inc. http://tech.unicosystem.com 314-481-9000 800-527-0896 sales@unicosystem.com





