

Twist-Fit System™

Available for 2"
(51mm) flexible
supply tubing



Features and Benefits

- Lock-and-release tabs for easy assembly
- Couplings attached to tubing at the factory
- Change outlet face plates in a snap
- Compatible with other high velocity products
- More ordering options to order exactly what you need for your project
- Reduce supply tube installation time by as much as 50%

System Advantages

- Fits any space
- Quiet Performance
- Little or No Remodeling
- Draft free, even temperatures
- Removes 30% more humidity
- Matches any decor
- Operating Efficiency



The **NEW** supply duct connection system
reduces the steps and time involved
in the installation process!



UNICO FITS

your **LIFE**

your **STYLE**

your **BUSINESS**



About Unico

Since its inception in 1985, **Unico, Inc.** has dedicated itself to the production of quality products for the indoor comfort market. This dedication has made **Unico, Inc.** a leading innovator in superior heating and air conditioning products and, most notably, the small-duct market.

Unico, Inc. is the leader in Small Duct High Velocity (SDHV) heating and cooling systems.

About Twist-Fit System™

Unico is always trying to improve and develop new and innovative equipment. We developed our new Twist-Fit System, which transformed our tubing and outlet products, thus resulting in reduced supply tube installation time by as much as 50%. The new Twist-Fit System is simpler, faster and easier to purchase ultimately saving you time, energy, and money, with little to no waste.

Consisting of lock-and-release tabs making it easier and faster to assemble, Twist-Fit couplings are attached to lengths of sound attenuator or aluminum supply tubing by threading the base of the coupling into the inner core of the tubing. The internal insulation and outer mylar jacket of the supply tubing are then tucked into the rim of the Twist-Fit and the connection is secured with UL-181B foil tape.*

**All tubing is supplied with couplings already attached from the factory.*

Matching Twist-Fit couplings are attached to the desired plenum take-offs, outlet registers, or additional lengths of supply tubing. To make a connection, simply line up the tabs to their corresponding slots and twist clockwise until a click is heard. At least one Twist-Fit connector must have a gasket to prevent leakage.



Contact Us

Unico, Inc.

1120 Intagliata Drive

Arnold, MO 63010

Phone : + 800-527-0896

Email : insidesales@unicosystem.com

Web : www.unicosystem.com

Fax : 314-457-9000

The Unico System®